



ALUMINUM OXIDE POLISHING SLURRY

Typical Physical Properties

- Appearance white slurry
- Particle Size(coulter) D50......1.9 – 2.2μm
- Baumé.....N/A
- Suspension Treated...... Yes

Applications

- Highly Concentrated Aluminum Oxide Based Slurry Precision Engineered for Universal Polishing applications: Digital/Free Form & Conventional Polishing
- High concentrated formulation designed to reduce costs associated with transportation and storage. Eliminate shipping of water based polishing compound and high transport costs!
- Slurry is Designed to be Diluted (at customer's laboratory) to desired Baumé Range of 30 to 12
- Higher Concentration Leads to Overall Lower Cost of Ownership. Reducing costs by 50% or more.

Packaging(G) 4 gal/case; 144 gal/pallet (P) 5 gal/pail; 24 pails/pallet Cautions Refer to Material Safety Data Sheet

295 Fifth Avenue New York, NY 10016 | Tel: 212 685 570 | Fax: 212 685 5719 |

mail@gkci.com www.gkci.com

The information herein is considered to be a fair representation of this product. The data are not to be interpreted as a specification or guarantee of properties. Gerard Kluyskens Company and Ferro Corporation make no implied warranties as to its accuracy and assumes no liability arising out of its use by others. The information does not constitute a license to use or infringe any patents.